




## General >> instructions

Read this installation guide carefully before starting the installation so that you will be able to use all the technical advantages of the systems and do not start with the installation before you have read and understood the instructions.

1. If you comply with the advice given below you will avoid an early termination of the product guarantee and you will be enjoying your product for years to come.
2. Never install the system if the ignition is on. Pull the ignition key.
3. After switching off the ignition, wait for 10 minutes until all electric devices and ECU are turned off.
4. If possible, install the module in a dry area in the engine compartment. Humidity and wetness contain minerals which cause corrosion to the electronic circuits. Fix the harness and protect it



**ATTENTION**



**IGNITION OFF**



**WAIT 10 MIN**



**KEEP AWAY ANY  
HEAT SOURCE**



**DON'T CHANGE  
THE SETTINGS**



**DO SPLASH  
PROOF INSTALL**



**REMOVE BEFORE  
ENGINE WASH**

5. Before every engine wash, remove the entire tuning system
6. Do not fix tuning systems to engine parts that could heat up. Never fix the module directly or close to the engine (engine block). High temperatures can reduce the lifespan of electronic devices and can deform or melt specific plastics-materials.
7. Take care that the harness does not touch the parts in motion and the metal parts to avoid friction. Do not make any changes to the harness (do not make it any longer or shorter).
8. Do not run together or tie the harness with fuel injection harness or abs harness that carries signal
9. In case of the malfunctioning of the system due to any non-compliance with the instructions during the installation of the tuning modules, the product guarantee will be terminated.



Harness WS-B 8220 Has 2 channel connection A and B both side Y shaped Connection it goes between sensor and harness. Please Locate your Intake manifold boost sensor and Turbo boost Sensor.